

MA控制台 MA Controller



技术参数

华硕主板, 英特尔酷睿 CPU, 8G内存,
SSD金士顿240g, 技嘉独立显卡
1个9寸触摸屏
2个15.4寸电动升降宽屏触摸显示屏
显示窗口固定鼠标不可拖动
支持物理按键关闭窗口运行其他灯光软件
9寸屏幕下X1-X20 User1 User2按键LED支持跟程序同步亮灯
支持Art-net网络扩展至256域, 无需NPU就可全部输出信号
可外接HDMI显示器1个
输入电压: 110V~220V 50~60Hz, 内置大功率UPS不间断电源
内置6个DMX-512输出接口, 1个DMX-512输入接口,
最大扩展可256DMX输出
一个高灵敏轨迹球
内置键盘抽屉
1个LTC时间码输入接口, 1个MIDI时间码输入接口
1个主控调光轮, 4个属性编码轮, 1个主控推杆, 2个AB推杆
15个程序回放推杆, 30个程序存储功能键
4个USB接口, 1个音频接口, 1个网络接口, 2个工作灯接口

TECHNICAL PARAMETER

ASUS motherboard, Intel Core CPU, 8G memory,
SSD Kingston 240g, Gigabyte discrete graphics
1 9 inch touch screen
Two 15.4-inch widescreen touch screens with electric lifting
The display window is fixed and the mouse cannot be dragged
Support physical buttons to close the window to run other lighting software
The X1-X20 User1 User2 button LED under the 9-inch screen
can be turned on synchronously with the program
Support Art-net network expansion to 256 domains,
all signals can be output without NPU
1 external HDMI display
Input voltage: 110V~220V 50~60Hz, built-in high-power
UPS uninterruptible power supply
Built-in 6 DMX-512 output interfaces, 1 DMX-512 input interface,
Maximum expansion of 256DMX output port
A highly sensitive trackball
Built-in keyboard drawer
1 LTC time code input interface, 1 MIDI time code input interface
1 main control dimming wheel, 4 attribute coding wheels,
1 main control fader, 2 AB faders
15 program playback faders, 30 program storage function keys
4 USB ports, 1 audio port, 1 network port, 2 work light ports



YZ-Tiger Touch

触摸老虎控制台

Tiger Touch Controller



鹅颈灯



背面图:



技术参数

采用功能强大新型直观的泰坦Tian操作系统
 强大的现场场景控制
 酷睿双核处理器, 60G固态硬盘, 4G内存
 支持中文菜单显示, 且内置多种语言
 反映灵敏的宽屏界面, 屏幕全触屏, 中英文界面
 内置15.4寸触摸屏, 可扩展17寸触摸屏
 4个DMX512输出端口, 2048个DMX通道
 支持Artnet,并可扩展至12个DMX输出口, 6144个通道
 20个场景及跑灯主控
 超过1000个虚拟重放
 与珍珠专家演出文件兼容
 10个宏按钮和宏库, 可编辑任何程序
 强大的CMY调色功能
 支持涂鸦式手写功能, 可预览服务器或数字的内置素材
 预留一个外部的wi-fi接入点, 可使用移动设备(IPhone、iPod Touch)
 进行远程遥控
 支持Artnet Avotalk和ctip协议支持
 支持CITP多媒体素材协议
 超过1000个世界主流灯具灯库,并内置Personality Builder灯库写入软件
 输入电压: 110V~220V 50/60Hz
 包装尺寸: 680*420*150mm

TECHNICAL PARAMETER


Tian operation system, strong scene control,
 Dual-Core Processor, 60G SSD, 4G memory
 Built-in multiple languages
 Sensitive wide interface, touchable and with both Chinese and English
 Built-in 15.4 inch touch screen, can expand to 17 inch
 4 DMX512 output, 2048 DMX channels
 Support Artnet, can extend to 12 DMX Output, 6144 DMX channels
 20 scenes or chase, More than 1 000 virtual replay
 Compatible with pearl performance files
 10 micro buttons and micro library, can make any program
 Excellent CMY color mixing function
 Support graffiti handwriting, can preview server or built-in digital material
 Reserved a external wi-fi access, can control remotely by mobile device
 (iPhone、iPod Touch)
 Support Artnet Avotalk and ctiP Protocol
 Support CITP multimedia material agreement
 More than 1000 world main lighting fixture library,
 built-in Personality Builder software
 Volt: 110V-220V 50/60Hz
 Packing size: 680*420*150mm



YZ-Pilot1024

领航1024控台


Pilot 1024 Controller



鹅颈灯



背面图:



技术参数

DMX512/1990标准,
共1024个DMX控制通道,
2个光电隔离DMX512信号输出,
可抗2000Vrms电气冲击
最多控制96台独立地址码或96路线, 使用珍珠R20灯库
内置效果发生器, 有135个内置图形,
方便用户做效果控制,
如画圆、螺旋、彩虹、追逐等多种效果。
图形参数(如: 振幅、速度、间隔、
波浪、方向)均可独立设置。
60个重演场景, 用于储存多场景和场景。
多场景最多可储存600步。
可同时运行10个场景
带背光的LCD显示屏, 支持中英文显示
U盘备份和升级。
专业鹅颈工作灯, 适合室内外演出使用。
电源: 110-240V 50/60Hz
尺寸: 485*420*105mm
重量: 10KG

TECHNICAL PARAMETER

DMX512/1990 standard, total 1024 DMX channels .
2 DMX signal Output, anti 2000VRMS electric shock
Can Control 96 lighting with independent address code
Or 96 dimmer routes, use pearl R20 fixture library
Built-in 135 effect generator, convenient for user to do effect control.
Such as circle, spiral, rainbow
Chase: Graphics parameter can be set independently
(such as: amplitude, speed, interval, wave, direction)
60 reply scene, used for storing multistep or single scene,
The max multistep scene is 600
10 scenes can run at the same time
LCD display with backlit, support Chinese and English
U disk backup and upgrade
Professional gooseneck light,
suitable for both indoor and outdoor performance
Volt: 110-240V 50/60Hz
Size: 485*420*105mm
Weight: 10KG

